



SUBMITTAL

2" - 4" DOUBLE WALL / SINGLE WALL VANE & RAIL

Omni Duct Systems Vanes and Vane Runners are constructed in accordance with SMACNA construction standards.

SINGLE WALL VANES

Duro Dyne VR2 or JVR2 Runner is used in construction of Single Wall
2" Vane constructed of 24 ga. Galvanized w/ spacing 1.5"
4" Vane constructed of 22 ga. Galvanized w/ spacing 3.25"

DOUBLE WALL VANES

Ductmate Pro Rail / Duro Dyne or equivalent is used in construction of Double Wall
2" Vane constructed of 26 ga. Galvanized w/ spacing 1.5"
4" Vane constructed of 24 ga. Galvanized w/ spacing 3.25"

***Note: Check to indicate variations from standard**

STYLE / TYPE

- 2" Single Wall
- 4" Single Wall

-
- 2" Double Wall
 - 4" Double Wall

MATERIALS

- Aluminum
- Stainless Steel

Optional Hat Section for Liner

- No
- Yes

www.omniduct.com

Job Name: _____

Location: _____

Mechanical Contractor: _____

Job No: _____

Manufacturer : **Omni Duct Systems, Toll Free (888) 444-DUCT (3828)**

Date: _____