

RECTANGULAR DUCT

Omni Duct Rectangular Duct & fittings are fabricated from galvanized steel and are constructed in accordance with the latest SMACNA construction standards.

Reference SMACNA tables 1"-10" WG for construction standards and reinforcement schedule

- Omni Rectangular Duct & Fittings meet ASTM-A653-96 standards
- 304 Stainless Steel - ASTM-A-240
- 316L Stainless Steel - ASTM-A-240
- Aluminum 3003H14 - ASTM-B-209
- Galvanized G90 Metal - ASTM-A-653-96

OPTIONS

JOINT CONNECTORS*

- S&D/SS&D
- TDC
- DUCTMATE

SEAM CONSTRUCTION*

- PITTSBURGH
- SNAP-LOCK

REINFORCEMENT OPTIONS*

- EXTERNAL ANGLE IRON
- INTERNAL TIE RODS

SEAM SEALANT AVAILABLE*

- YES
- NO

*Note: Check to indicate variations from standard

COIL LINE FINISH LENGTHS

CONNECTORS	60"	48"
TDC/TDC	56-1/4	44-1/4
TDC/S&D	57-5/8	45-5/8
TDC/DM35	58-1/8	46-1/8
TDC/RAW	58-1/8	46-1/8
TDC/CAPS	57-1/2	45-1/2
TDC/CAPL	57-1/8	45-1/4
TDC/NOTCH	57-1/8	45-1/8
S&D/S&D	59	47
S&D/DM35	59-1/2	47-1/2
S&D/RAW	59-1/2	47-1/2
S&D/CAPS	58-7/8	46-7/8
S&D/CAPL	58-5/8	46-5/8
S&D NOTCH	58-1/2	46-1/2
RAW/RAW	60	48
CAPS/RAW	59-3/8	47-3/8
CAPL/RAW	59-1/8	47-1/8
CAPS/CAPS	58-3/4	46-3/4
CAPL/CAPL	58-1/4	46-1/4
DM35/DM35	60	48

LAST MODIFIED: 06/25/20